


CONSTRUCT (5) FIRE HYDRANTS IN THE PINAL VALLEY WATER SYSTEM

SE 1/4 SEC. 13, T. 06 S., R. 05 E. OF THE G. & S. R. B. & M.

GENERAL NOTES:

- ALL WORK AND MATERIALS SHALL CONFORM TO CURRENT COUNTY HEALTH DEPARTMENT STANDARDS AND REVISIONS ARIZONA WATER COMPANY STANDARD SPECIFICATIONS AND DETAILS, AND ARIZONA DEPARTMENT OF ENVIRONMENTAL QUALITY ENGINEERING BULLETIN NO. 10.
- PERMITS REQUIRED WILL BE SECURED FROM THE APPROPRIATE AGENCY, I.E. COUNTY PERMIT IN COUNTY RIGHT-OF-WAY.
- PRIOR TO CONSTRUCTION, THE APPROPRIATE AGENCY(IES) WILL BE NOTIFIED AS REQUIRED BY THE PERMIT(S).
- ALL BACKFILL COMPACTION AND TESTING SHALL BE PER CURRENT COUNTY, CITY, STATE, ADOT, AND ARIZONA WATER COMPANY STANDARDS AND SPECIFICATIONS.
- ALL WATER LINES 8" AND LESS ARE TO HAVE A MINIMUM COVER OF 36 INCHES & ALL WATER LINES 12" AND GREATER ARE TO HAVE 48" OF MINIMUM COVER OVER THE TOP OF PIPE TO FINISHED GRADE, UNLESS OTHERWISE SPECIFIED ON THE CONSTRUCTION DRAWINGS.
- ALL FRAMES, COVERS, VALVE BOXES, ETC. SHALL BE ADJUSTED TO FINISHED GRADE PRIOR TO PLACING OF ASPHALTIC CONCRETE SURFACE COURSE BY THE CONTRACTOR. (WHERE APPLICABLE)
- ALL WATER LINES SHALL BE PRESSURE AND LEAKAGE TESTED IN ACCORDANCE WITH AWWA C-600 OR MAG STD. 611.2.
- ALL WATER LINES ARE TO BE DISINFECTED PER ADEQ ENGINEERING BULLETIN NO.8 OR AWWA C651-05 OR MAG 611.3.
- AIR RELEASE VALVES ARE REQUIRED AT WATER SYSTEM HIGH POINTS PER ARIZONA WATER COMPANY STANDARD DETAILS.
- WATER/SEWER SEPARATION SHALL BE PER CURRENT ARIZONA WATER COMPANY STANDARDS AND ADEQ AAC R18-5-502-C.
- IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO UNCOVER ALL EXISTING WATER LINES BEING CONNECTED TO, AND TO VERIFY THE LOCATION, DEPTH AND SIZE OF PIPE BEFORE ANY CONSTRUCTION BEGINS.
- ANY CONSTRUCTION PERFORMED WITHOUT THE KNOWLEDGE OF THE INSPECTOR OR HIS REPRESENTATIVE IS LIABLE FOR REMOVAL AND REPLACEMENT AT THE CONTRACTOR'S EXPENSE.
- IN ACCORDANCE WITH AAC R18-4-213, ALL MATERIALS ADDED AFTER JANUARY 1, 1993 WHICH MAY COME IN CONTACT WITH DRINKING WATER, SHALL CONFORM TO NATIONAL SANITATION FOUNDATION STANDARDS 60 AND 61.
- ALL WATER SERVICES SHALL BE SET A MINIMUM OF 2 FEET ON THE CUSTOMERS PROPERTY AND NOT WITHIN RIGHT-OF-WAY.
- UNLESS OTHERWISE SPECIFIED ON THE CONSTRUCTION DRAWINGS, ALL WATER MAINS ARE TO BE INSTALLED 5 FEET FROM THE PROPERTY LINE INSIDE THE RIGHT-OF-WAY OR EASEMENT.
- WATER VALVES SHALL BE SPACED NOT MORE THAN 500 FEET IN COMMERCIAL DISTRICTS AND NOT MORE THAN 800 FEET IN OTHER DISTRICTS. VARIATIONS MAY BE REQUIRED FOR TRANSMISSION MAINS OR SPECIAL APPLICATIONS. SUFFICIENT VALVING IS REQUIRED WHERE WATER LINES CROSS STREAMS, RAILROADS AND MAJOR HIGHWAYS.
- MAXIMUM JOINT DEFLECTION FOR 6" MECHANICAL JOINT DUCTILE IRON PIPE IS 7°-7' OR 27° FOR 18 FOOT LENGTH PIPE, FOR A MAXIMUM CURVE OF 145 FEET.
- MAXIMUM JOINT DEFLECTION FOR 6", 8", & 12" PUSH-ON JOINT DUCTILE IRON PIPE IS 5° OR 19° FOR 18 FOOT LENGTH PIPE, FOR A MAXIMUM CURVE OF 205 FEET.
- MAXIMUM JOINT DEFLECTION FOR 8" & 12" MECHANICAL JOINT DUCTILE IRON PIPE IS 5°-21' OR 20' FOR 18 FOOT LENGTH PIPE, FOR A MAXIMUM CURVE OF 195 FEET.
- ALL PIPE, FITTINGS, VALVES, FIRE HYDRANTS, AND OTHER APPURTENANCES MUST CONFORM TO AWWA, ASTM, AND NSF STANDARDS (EB 10, CHAP. 7, SECTION B).
- BACKFLOW PREVENTION MUST BE IN ACCORDANCE WITH R-18-4-115.
- CONSTRUCTION MATERIALS USED IN WATER SYSTEM MUST BE LEAD FREE AS PER AAC R18-4-504 AND R18-1-101 (43).



WATER MAIN MATERIALS
ABBREVIATION REFERENCE:
CA - CEMENT ASBESTOS
PVC - POLYVINYL CHLORIDE
CLC - CEMENT LINED AND COATED STEEL
CU - COPPER
STL - STEEL
CI - CAST IRON
DI - DUCTILE IRON
HDPE - HIGH DENSITY POLYETHYLENE
GS - GALVANIZED STEEL

OWNER/ENGINEER/DEVELOPER
ARIZONA WATER COMPANY
POST OFFICE BOX 29006
PHOENIX, AZ 85038-9006
VOICE: (602) 240-6860
FAX: (602) 294-2169
CONTACT: AMY WALTHERESON

BASIS OF BEARING
IS THE SOUTH LINE OF THE SOUTHEAST QUARTER
OF SECTION 13 SHOWN HEREON AS S89°53'04" W
BENCHMARK
NCS CONTROL POINT E422
BEING A 3.5" BRASS DISK STAMPED "E 422 1980"
ELEVATION = 1419.96' NAVD88 DATUM. NCS DATA.

REFERENCE DOCUMENTS
(R1) PLAT OF COTTONWOOD GARDENS AS RECORDED
IN BOOK 19 OF MAPS, PAGE 22.

CITY OF CASA GRANDE PLAN APPROVAL RECOMMENDED

CIVIL ENGINEER: _____
DATE: _____ EXPIRATION DATE: _____

THE CITY APPROVES THESE PLANS IN CONCEPT ONLY.
THE CITY ACCEPTS NO RESPONSIBILITY FOR ERRORS OR OMISSIONS.

CITY OF CASA GRANDE PLAN APPROVAL

CIVIL ENGINEER: _____
DATE: _____ EXPIRATION DATE: _____

THE CITY APPROVES THESE PLANS IN CONCEPT ONLY.
THE CITY ACCEPTS NO RESPONSIBILITY FOR ERRORS OR OMISSIONS.

"AS-BUILT CERTIFICATION"

ACCEPTED BY: _____
CITY ENGINEERING INSPECTOR: _____ DATE: _____
CITY ENGINEER: _____ DATE: _____

THE CITY APPROVES THESE PLANS IN CONCEPT ONLY.
THE CITY ACCEPTS NO RESPONSIBILITY FOR ERRORS OR OMISSIONS.

SHEET INDEX			
SHT. No.	DWG. No.	DESCRIPTION	PREPARED BY
1	PV-0341	COVER SHEET	AWC
2	PV-0341	CONSTRUCTION PLAN	AWC
3	PV-0341	AWC NOTES	AWC
4	PV-0341	AWC DETAILS	AWC
5	PV-0341	CITY OF CASA GRANDE NOTES	AWC

QUANTITIES LIST		
	QUANTITY	REVISIONS
1	5	1
2	53 LF	1
3	10	1

CONSTRUCTION NOTES:

- CONNECT MJ FITTINGS TO MJ FITTINGS USING FOSTER ADAPTERS.
- ALL MATERIALS & PIPE REMOVED, MUST BE DISPOSED BY THE CONTRACTOR.
- ASPHALT REPLACEMENT & TRENCH BACKFILL PER MAG 200-1 ON SHT. 4 IF NECESSARY
- ALL RESTRAINED PIPE MUST BE U.S. PIPE TR FLEX, AMERICAN FLEX, RING OR DUCTILE IRON PIPE WITH MEGALUG SERIES 1100, STAR GRIP SERIES 3000 OR TUF GRIP SERIES 3000 JOINT RESTRAINTS.
- USE MEGALUG SERIES 1100, STAR GRIP SERIES 3000 OR TUF GRIP SERIES 1000 JOINT RESTRAINTS AT ALL MJ FITTING CONNECTIONS.
- INTERRUPTION OF WATER SERVICE FOR TIE-INS CANNOT EXCEED 4 HOURS IN DURATION FROM TIME OF SHUTDOWN TO COMPLETION OF FLUSHING.
- COMPANY DOES NOT GUARANTEE EXISTING VALVES WILL PROVIDE A DRY SHUTDOWN.
- AN ADDITIONAL FITTINGS REQUIRED FOR TIE-INS BUT NOT SHOWN ON PLANS OR PROPER ALIGNMENT SHALL BE CONSIDERED INCIDENTAL AND INCLUDED IN THE PIPE PRICE.
- PROTECT ALL UTILITY CROSSINGS IN PLACE UNLESS OTHERWISE NOTED ON PLANS.
- TRAFFIC CONTROL PER RIGHT-OF-WAY PERMIT REQUIREMENTS.
- CONTRACTOR MUST USE NO. 1 METER BOXES WHEN INSTALLING A NEW SERVICE CONNECTION AT THE SAME LOCATION OF AN EX. SERVICE.
- CONTRACTOR MUST MAINTAIN MIN. 3-FEET HORIZONTAL SEPARATION FROM OUTSIDE EX. POWER POLES IF NECESSARY DURING CONSTRUCTION.
- CONTRACTOR MUST PLUG ENDS OF ABANDONED IN PLACE WATER MAINS WITH CLASS C CONCRETE MIN. 24-INCHES INTO PIPE.
- PASSING COMPACTION TEST RESULTS ARE REQUIRED PRIOR TO PAVEMENT REPLACEMENT.
- CONTRACTOR MUST PAY THE COST OF ALL WATER PROVIDED BY AWC TO THE CONTRACTOR FOR CONSTRUCTION AND TESTING OF THE WATER MAINS.
- CONTRACTOR MUST PROVIDE AND INSTALL NEW CUSTOMER SHUTOFF VALVE AT EACH SERVICE WITH PRIOR CUSTOMER PERMISSION.
- CONTRACTOR MUST COORDINATE MATERIAL, LOCATION, AND TIMING, OF SERVICE TIE-OVERS WITH CUSTOMER.
- PROTECT WATER LINE TO BE ABANDONED IN PLACE UNTIL FINAL TIE-INS ARE COMPLETED.
- CONTRACTOR HAS THE OPTION TO BORE THE ROAD WHILE MAINTAINING MINIMUM DEPTH FOR SERVICE REPLACEMENT.
- CONTRACTOR MUST MAINTAIN ALL PAVEMENT CUTS IN A SMOOTH AND SAFE MANNER WITH FLUSH MOUNTED PLATES OR TEMPORARY ASPHALT UNTIL CONTRACTOR COMPLETES PERMANENT PAVEMENT REPLACEMENT.
- CONTRACTOR MUST MATCH PAVEMENT THICKNESS PER MAG STD. DTL. 200-1 IF THE EXISTING PAVEMENT IS 10" THICKER THAN 30" INCHES, 3" MINIMUM SHALL BE PUT BACK WITH EITHER R-19 3/4" HOT MIX OR R-12 1/2" HOT MIX. EDGES WILL BE TACK COATED PRIOR TO THE MIX BEING PLACED, AFTER PATCH IS COMPLETE A CRACK SEAL SHALL BE PLACED AROUND THE SAW CUT LINES AND PATCH.
- CONTRACTOR MUST CONFORM TO MAG STD. DTL. 200-2 SECTION 336 (F-G) IN PINAL COUNTY R/W
- REPLACE EXISTING LANDSCAPING IN KIND AFTER CONSTRUCTION IS COMPLETE

ARIZONA WATER COMPANY

3805 N. BLACK CANYON HWY. POST OFFICE BOX 29006
PHOENIX, ARIZONA 85038-9006
(602) 240-6860

PROJECT SHEET DESC: CONSTRUCT (5) FIRE HYDRANTS IN THE PINAL VALLEY WATER SYSTEM

P.E. No.: 2594	SYSTEM: PINAL VALLEY (CG)
LEGAL DESC: SE 1/4 SEC. 13, T. 06 S., R. 05 E.	TAX DIST.: 0428 & 0458
DATE: 01/12/2026	SCALE: AS SHOWN
DRAWN BY: TDS	REVIEWED BY: <i>ml</i>
CHECKED BY: <i>ml</i>	
DWG. No.: PV-0341	
PROJECT SHEET DESC: COVER SHEET	


Registered Professional Engineer
CERTIFICATE NO. 70873
AMY WALTHERESON
State of Arizona
Arizona Water Company
Expires 3-31-2026

FOR BIDDING PURPOSES ONLY
Feb 12, 2026

Engineering Department
Arizona Water Company

PV-0341

SHEET 1 OF 5



E-8-1
CONSTRUCTION SPECIFICATIONS
FOR THE INSTALLATION OF WATER DISTRIBUTION SYSTEMS
DUCTILE IRON

DEFINITIONS

A. **Company.** The words "Company" or "Arizona Water Company" mean Arizona Water Company, and where applicable, any division of Arizona Water Company, whose principal place of business is located at 3805 North Black Canyon Highway, Phoenix, Arizona 85015-5351 (Post Office Box 29006, Phoenix, Arizona 85038-9006).

B. **Company's Authorized Representative.** The words "Company's Authorized Representative" mean any officer of the Company, and any of the Company's Engineers, any Division Manager or Superintendent of the Company and/or such other persons designated in writing as the "Company's Authorized Representative" by the President or any Vice President of the Company.

C. **Contractor.** The word "Contractor" means either an individual or other entity employed to do the work as shown on the Construction Drawings and as specified herein.

D. **Construction Drawings.** The words "Construction Drawings" mean plans prepared by or on behalf of Arizona Water Company.

E. **Contract.** The word "Contract" means the written document titled "Proposal/Contract" when such document has been signed by an officer or other authorized representative of both the Contractor and the Company.

1. GENERAL

All work is to be completed in a safe, workmanlike manner and in accordance with these Construction Specifications; any deviation therefrom must be approved in writing by the Company.

Installations must conform with the requirements of all governmental regulating agencies and the cost of conforming to such regulations must be included in the unit bid prices. Examples of such regulations, without attempting to be inclusive, are:

- a. Special compaction and paving for street crossing.
- b. Shoring when required because of the trench depth.
- c. Closing a trench in those areas where no open trench is allowed overnight.
- d. Barricading and traffic controls required.

2. LOCATION MARKING

Alignment stakes as required in the opinion of the Company shall be furnished by the Company to the Contractor and shall be set by the Company at agreed upon intervals and offsets. Under normal circumstances these will represent the pipeline location five feet (5') into the right-of-way measured from property pins. Grade stakes will be provided only when the Construction Drawings show a pipeline depth other than covered in these Specifications. It is the responsibility of the Contractor to preserve all survey work.

3. TRENCH EXCAVATION

The trench location is to be determined by the Construction Drawings.

FOR 2-INCH OR SMALLER PIPE: The depth of the trench prior to pipe laying shall be such that the finished pipeline shall have between thirty-six inches (36") and forty-two inches (42") of cover unless otherwise specified on the Construction Drawings.

FOR 12-INCH AND LARGER PIPE: The depth of the trench prior to pipe laying shall be such that the finished pipeline shall have between forty-eight inches (48") and sixty inches (60") of cover unless otherwise specified on the Construction Drawings.

The width of the trench at and below the level of the top of the pipe shall be a minimum of twelve inches (12") plus the outside diameter of the pipe barrel and a maximum of twenty-four inches (24") plus the outside diameter of the pipe barrel.

The bottom of the trench shall be accurately graded to provide a uniform bearing for each length of pipe for the full length of the pipe. If the native material on the trench bottom can be reasonably dug by hand, bellholes shall be dug for the joints so that the joints in no way support the pipe. When native materials such as rock are encountered during trenching that will not provide a uniform support for the pipe, the trench will be over-excavated on additional six inches (6") and suitable bedding material will be placed in the trench.

Bedding material will be placed by hand in four-inch (4") lifts and compacted to ensure uniform compaction and to eliminate any voids under the pipe. When the space between the pipe and trench bottom varies, this must be backfilled and compacted in four-inch (4") lifts to the mid-section of the pipe.

Whenever the trench is over-excavated for whatever reason, the trench bottom will be brought up to the correct depth at the Contractor's expense using either method (a) or (b) as follows:

a. A.B.C. material shall be used and compacted to a uniform density of not less than 95% of the maximum density as determined by M.A.G.

b. Native material 100% of which will pass through a one and one-half inch (1-1/2") screen and at least 20% of which will pass through a number-8 screen shall be used and compacted to a uniform density of not less than 85% of the maximum density as determined by AASHTO T-99 method A and T-191.

4. MATERIALS TO BE PROVIDED BY CONTRACTOR

Unless otherwise specified on the Construction Drawings or in the Contract, the Contractor will supply all of the necessary materials which will become a permanent and integral part of the water distribution system, including concrete blocking, anchors, backfill material, paving material and supplies used during the prosecution of the work. All materials provided by the Contractor to construct the water distribution system must be NSF Standard 61 approved. All potable water pipes and fittings shall have NSF-PW seal. Construction materials used in the water system shall be lead free as defined at AAC R2B-4-504 and R1B-1-101. The Contractor will provide the following materials:

a. FIRE HYDRANTS: Mueller Super Centurion 250 Fire Hydrant, meets ANSI/AWWA C502 Standard, Model No. A-423, 5-1/4" main valve opening, three way, 6" Mechanical Joint Shoe, 1-1/2" pentagon operating nut, color - yellow, drain open, open direction - left, 4" or 4-1/2" bury depending on application. For pumper and hose nozzle information see below.

(1) One - 4" Pumper Nozzle, NST and Two - 2-1/2" Hose Nozzles, NST. (These locations only: Ajo, Casa Grande, Coolidge and San Manuel.)

(2) One - 4-1/2" Pumper Nozzle, NST and Two - 2-1/2" Hose Nozzles, NST. (These locations only: Apache Junction, Arizona City, Lakeside, Oracle, Overgaard, Pinewood, Rimrock, Sedona, Sierra Vista, White Tank and Winkelman.)

(3) One - 4-1/2" Pumper Nozzle, NST and Two - 2-1/2" Hose Nozzles, NPT (Bisbee only.)

(4) One - 3" Pumper Nozzle GA-350 (6 threads per inch, 3.50 pitch diameter) and Two - 2-1/2" Hose Nozzles, NPT (Miami only.)

(5) One - 3-1/2" Pumper Nozzle GA-6-411 (6 threads per inch, 4.11 pitch diameter) and Two - 2-1/2" Hose Nozzle, NST (Superior only.)

b. FITTINGS: Manufactured by Tyler or Union. Crosses, Elbows, Tees, Caps, Reducer, Adapter, Plug, Blind Flange and Tapped Flange: Ductile Iron, Class 350, SSB, Cast Iron Cement Lined.

(1) Foster Adapters for MAG, made by Infact Corporation: Available in size 4" to 16". Part No. 4" - 4FA-BC, 6" - 6FA-BC, 8" - 8FA-BC, 10" - 10FA-BC, 12" - 12FA-BC, 16" - 16FA-BC.

c. DETECTOR CHECK VALVE: Mueller/ Hersey EDC III, iron body, including 5/8" x 3/4" Trim Kit, Trim Kit Part No: 4" - 282080, 6" - 282082, 8" - 282085, 10" - 282496.

d. GATE VALVES: Mueller Resilient Wedge Gate Valves, meets AWWA C509 specification, 250 psig, Non-rising stem, Part No. A-2360 sizes 4" through 12"; Part No. A-2361 sizes 14" through 36", low zinc stems, epoxy coated inside and outside to meet the NSF 61 rating. The bonnet and stuffing box shall have 304 stainless steel bolts/nuts.

e. TRACER WIRE and WARNING TAPE:

- (1) TRACER WIRE: Shall be direct bury AWG #14 solid copper wire, Color: Blue.
- (2) WARNING TAPE: Reel Industries, Standard Terra Tape in 3" widths, Color: Blue and imprinted "Arizona Water Company".

f. AIR RELEASE VALVE: Crispin Model AR10 with 1" NPT inlet and 1/2" NPT outlet, cast iron body and top flange with a 5/64" orifice with stainless steel valve seats and Buna-N rubber.

g. PRESSURE RELIEF VALVE: Watts 174A, Model M, 2" inlet, 2"

h. MEGALUG: Mechanical Joint restraint mode of ductile iron conforming to ASTM 536-80, 250 psi made by EBAA Iron, Inc., series 100 or equal.

i. METER BOXES:

- (1) Concrete Box with a steel regular lid, Number 1: Tucson specification.
- (2) Concrete Box with a steel regular lid, Number 2, 3, and 4: Phoenix specification.

j. PIPE, COPPER: Type K soft copper in 60 or 100-foot coils, per ASTM B88.

k. PIPE, DUCTILE IRON: Ductile Iron Pipe, Cement Lined, Push-on, conform to current ANSI/AWWA Specification A21.5/C151, Pressure Class 350 (sizes 4" through 12"), Pressure Class 250 (sizes 14" through 20"), or Pressure Class 200 for 24" through 36" pipe, Vendors:

- (1) Pacific States Cast Iron Pipe Company
- (2) Griffin Pipe
- (3) United States Pipe and Foundry Company
- (4) American Ductile Iron Pipe
- (5) Clay Pipe (McWane, Inc.)

l. PIPE, PLASTIC: Plastic pipe, C-900 PVC per ANSI/AWWA C900, Class 150, sizes 6" through 12", NSF61 approved. Furnished in laying lengths of 20'. The barrel shall conform to the outside dimensions of steel pipe (IPS) or cast iron (CI) pipe equivalent and the wall thickness of dimension-ratio (DR) 18.

m. POLYETHYLENE ENCASEMENT (Polywrap): For pipeline and related fittings installed, EXCEPT for the Coolidge Division. Minimum .8 MI. and installed per AWWA C105/A21.5-93 and ASTM A-674-89. Manufactured by the Pacific States Cast Iron Pipe Company. The wrapping tape shall be minimum 10 mil. vinyl tape. No duct tape shall be used.

n. COUPLING: Mueller, straight three part union, tested to meet ANSI/AWWA C800, H1543, conductive compression.

Mueller, H15428, straight coupling, conductive compression by male iron pipe, tested to meet ANSI/AWWA C800 specification, Size: 2".

Mueller, H15451, straight coupling, conductive compression by female iron pipe, tested to meet ANSI/AWWA C800 specification, Size: 2".

Viking Johnson brand, sold by Mueller: MaxiFit Straight (2"-24"), MaxiFitXtra Straight (4"-8") and MaxiStep Transition, tested to meet AWWA/C.19-91 specifications - certified to ISO 9001:1994 / Smith - Blair Quantum.

o. STOP, ANGLE METER, BALL: Mueller, valve, B24258, conductive compression by meter swivel seat, tested to meet ANSI/AWWA C800, size 5/8" x 3/4" x 3/4" x 3/4" for a 3/4" service or size 1" for a 1" service.

p. STOP, CORP: Mueller, ball valve, B25008, taper thread by conductive compression, tested to meet ANSI/AWWA C800 specification, sizes: 3/4", 1" and 2".

Mueller, ball valve, B25028, iron pipe thread by conductive compression, tested to meet ANSI/AWWA C800 specification, sizes: 3/4", 1" and 2".

Mueller, 300 Ball Curb Valve, B-25122, taper thread by conductive compression, tested to meet ANSI/AWWA C800 specification, size: 2", 12" service

q. STOP, CURB-Orise valve, H10291, iron pipe thread by iron pipe thread, quarter turn check, brass, tested to 300 psi working pressure, tested to meet ANSI/AWWA C800 specification, size: 2".

Mueller, B20283, Mueller 300 ball curb valve, female iron pipe by female iron pipe, quarter turn check, tested to meet ANSI/AWWA C800 specification, Size: 2". (Blow-off E-9-8-1).

r. TAPPING SADDLE: Smith Blair, Cast Bronze ASTM-B584, 85-5-5-5, double strap, iron pipe threads, Models 321 and 323. Washers are silicon bronze, ASTM-B36. Gaskets are grade 60 Buna N, or Mueller bronze double strap saddle, BR 2 B series, cast bronze, ASTM-B585, 85-5-5-5, or H16084, 200 psig, meets ANSI/AWWA C800.

s. TAPPING SLEEVE: Mueller H304 Stainless Steel Tapping Sleeve, JCM 432 18.8 Type 304 Stainless Steel Tapping Sleeve, Romac "SST" Type 304 Stainless Steel Tapping Sleeve or CASCADE-style CST-EX stainless steel pressure-rated tapping sleeve.

t. TAPPING VALVE: Mueller Resilient Wedge tapping valve, Catalog Number T-2360-16, Class 125, sizes 4" through 12", Class 125, sizes 14" to 36" all with Type 304 stainless steel fasteners; bypass valves are required on 18" - 36" valves flange by mechanical joint per ANSI/AWWA C111, iron wedge, non-rising stem. Epoxy coated interior/exterior per ANSI/AWWA C550 for NSF 61 compliance, 250 PSIG range for valves 4" to 12", 150 PSIG range for valves 14" to 36".

u. U-BRANCH: Mueller, H15364, 1" male iron pipe by 3/4" male iron pipe, tested to meet ANSI/AWWA C800 specification. Size: 1" x 3/4" x 13-1/2", straight line.

v. VALVE BOXES: Valve Box with Cover, adjustable, Tyler 562-A or equal, made of cast iron.

w. VAULTS: Utility Vault Company, Chandler, AZ.

(1) 444-VA concrete vault with a 3660 aluminum double torsion door with a recessed padlock hasp, two - 18" x 24" center knockouts.

(2) 575-VA concrete vault with a 4874 aluminum double torsion door with a recessed padlock hasp, two - 18" x 24" center knockouts.

x. VALVE, METER: Mueller, B24265-1, Mueller 300 ballangle meter valve, female iron pipe by meter nut, quarter turn check, lock wing, tested to meet ANSI/AWWA C800 specification. Size: 1".

Mueller, B25170, Mueller 300 ball straight valve, conductive compression by female iron pipe, quarter turn check, lock wing, tested to meet ANSI/AWWA C800 specification. Size: 1".

y. YOKES, METER: Relocator type copper meter yoke with horizontal inlet and outlet and meter thread ends, B24118, with lock wing Mueller 300 angle ball valve, full port, sizes: 1" x 12", 5/8" x 3/4" x 7", 5/8" x 3/4" x 9".

Mueller, 2" copper meter yoke with horizontal inlet and outlet and female iron pipe threads, B2423-99000, with lock wing Mueller 300 ballangle meter valves on inlet and outlet risers. Raised 1" by-pass with lock wing Mueller 300 valve.

The Contractor also will be required to provide the following materials, the cost of which will be included in its unit bid price:

All material and concrete, for thrust blocks, other anchors, reinforcing steel, all gravel, crushed stone, A.B.C., earth, sand, or screened material which may be required; all material for bracing and shoring trenches and for construction of forms; all barbed wire and traffic control equipment; all material for paving replacement and any water used for compaction of backfill.

5. INSTALLATION OF MATERIALS

All materials are to be installed in accordance with manufacturers recommendations unless otherwise directed by these Specifications.

Al pipe, fittings and valves shall be laid true to the lines, grades and locations established by the Specifications and the Construction Drawings.

The ends and inside of the pipe shall be thoroughly cleaned and inspected for damage. No damaged materials shall be installed in the water distribution system. Whenever the work ceases for any reason, all open pipeline ends shall be tightly plugged by the Contractor. Plugs shall be watertight and approved by the company.

Concrete thrust blocks of the sizes required by the plans and specifications are to be provided of all valves, changes in direction or size, or at any other point where an unbalanced thrust due to water pressure would exist. Thrust blocks are to be formed to prevent any concrete from spilling over or into a joint.

Trench curves as shown on the Construction Drawings may be made without fittings when using push on joint pipe up to twelve inches (12") in diameter, if the deflection of the pipe does not exceed five degrees (5') or nineteen inches (19") per eighteen-foot (18') length of pipe. The minimum radius of such curves will be two hundred five feet (205').

Prior to construction, the appropriate agency(ies) will be notified as required by the permit(s).

It shall be the Contractor's responsibility to uncover all existing water lines being connected to, and to verify the location, depth and size of pipe before any construction begins.

Any construction performed without the knowledge of the duly authorized representative is liable for removal and replacement at the Contractor's expense. All fire hydrants, frames, covers and valve boxes, etc. shall be adjusted to finished grade prior to the placing of the asphalt concrete surface course by the Contractor (where applicable).

Air release valves shall be installed at water system high points per Standard Detail E-9-8-2/E-9-8-3.

Al water services shall be set a minimum of two feet (2') on the customer's property, preferably within the P.U.E. and not within right-of-way.

Unless otherwise specified on the construction drawings, all water mains shall be installed five feet (5') from the property line inside the right-of-way or easement.

Water valves shall be spaced not more than five hundred feet (500') in commercial districts and not more than eight hundred feet (800') in other districts. Variations may be required for transmission mains or special applications.

Installation of water line casing shall be per Standard Specification E-9-24-1.

Tracer Wire and Warning Tape are to be installed on mains, tees, crosses, ell's and fire hydrant laterals. They will not be installed on service lines. The tracer wire will be installed on the main 45 degrees from the vertical centerline of the pipe and shall be taped to the fittings directly and the main every 10 feet using a minimum 10 mil. vinyl tape. The tracer wire shall be placed above the valve riser and box with a minimum of 12" of wire inside. The warning tape shall be installed a minimum of two feet below the surface, being measured from final grade, directly over the center of the pipe. Any splices in the warning tape shall be joined using waterproof connectors.

Any splices in the warning tape shall be joined using minimum 10 mil. vinyl tape. The tracer wire shall be tested for continuity after backfill and compaction, but before paving. Any detected damages to the wire shall be repaired before paving will be allowed.


6. BACKFILL OF WATER MAIN TRENCHES

Backfill of any excavation shall conform to the requirements of any of the governmental agencies having jurisdiction over the location. If no governmental agency having such jurisdiction specifies backfill or compaction requirements, and no special requirements are shown on the Construction Drawings, the procedure set forth in this section will apply for water line trenches.

The bedding material above the pipe and backfill material shall be compacted to a minimum of 95

FOR 6" THROUGH 12" GATE VALVES
Mueller Resilient Wedge Gate Valves
Catalog Number A-2360
ANSI/AWWA C509 Compliant

FOR 14" THROUGH 16" GATE VALVES
Mueller Resilient Wedge Gate Valves
Catalog Number A-2361
ANSI/AWWA C509 Compliant



NON-VEHICULAR VALVE BOX


CONCRETE VALVE BOX
For Areas Subject To Vehicular Traffic

NOTE:

- The Valve Box Shall Be Adjusted To Finished Grade Prior To Placing Of Asphalt And/Or Concrete.
- For Non-Traffic Areas Use Tyler/Union 562-A Two-Piece 8855 Series Or Equivalent Adjustable Cast Iron Valve Box And Cover. Valves 4" To 12".
- All Valves Installed On Pipe Five Feet (5') Deep And Greater Are To Be Installed With A Valve Operator Extension, Mueller Catalog No. A-26441 And Shall Have A Debris Cap.
- Use Minimum Class 'C' Concrete which is defined as concrete whose minimum compressive strength at 14 days reaches 1600psi and at 28 days reaches 2000psi. per MAG Section 725, Table 725-1.

All Valves Installed On Pipe Five Feet (5') Deep And Greater Are To Be Installed With A Valve Operator Extension, Mueller Catalog No. A-26441.

ASPHALT VALVE BOX
For Areas Subject To Vehicular Traffic




CROSS SECTION TYPICAL


THRUST BLOCK SCHEDULE

PIPE SIZE	TEE, 45°, AND 22.5° ELLS, & PLUGS	90° ELLS
6" And Under	4 Sq.Ft.	6 Sq.Ft.
8"	6 Sq.Ft.	9 Sq.Ft.
12"	13 Sq.Ft.	20 Sq.Ft.
16"	23 Sq.Ft.	32 Sq.Ft.
18" And Larger	Calculated Per Project	

NOTES: All Bolts, Nuts and Drill Holes Shall Be Kept Free Of Concrete



ARIZONA WATER COMPANY



ARIZONA WATER COMPANY


The installation shown is to be installed in accordance with the Arizona Water Company standard specifications on file with the Arizona Department of Environmental Quality
Arizona Water Company
Arizona Water Company

Arizona Water Company

ARIZONA WATER COMPANY

STANDARD SPECIFICATION
FOR THE INSTALLATION OF
TYPICAL VERTICAL GATE VALVES

DRAWN BY: CB APPROVED BY: MW DATE: 03.20.1986 □ 08.23.2006 E-9-2-1



"T TOP" TRENCH REPAIR
(USE FOR TRANSVERSE TRENCH REPAIRS, SEE DETAIL 200-2)

TYPE "A" TRENCH REPAIR
(USE FOR LONGITUDINAL TRENCH REPAIRS, SEE DETAIL 200-2)

TYPE "B" TRENCH REPAIR
(USE FOR TRANSVERSE TRENCH REPAIRS IF SPECIFIED BY AGENCY)

TYPE "C" TRENCH REPAIR
(USE FOR LONGITUDINAL TRENCH REPAIRS, SEE DETAIL 200-2)

TYPE "D" TRENCH REPAIR
(TRENCH NOT UNDER CONCRETE OR ASPHALT PAVEMENT)

TYPE "E" TRENCH REPAIR
(TRENCH IN FUTURE ROADWAY PRISM OR ALLEY)

TYPE "F" TRENCH REPAIR
(TRENCH NOT UNDER CONCRETE OR ASPHALT PAVEMENT)

TYPE "G" TRENCH REPAIR
(TRENCH NOT UNDER CONCRETE OR ASPHALT PAVEMENT)

TYPE "H" TRENCH REPAIR
(TRENCH NOT UNDER CONCRETE OR ASPHALT PAVEMENT)

TYPE "I" TRENCH REPAIR
(TRENCH NOT UNDER CONCRETE OR ASPHALT PAVEMENT)

TYPE "J" TRENCH REPAIR
(TRENCH NOT UNDER CONCRETE OR ASPHALT PAVEMENT)

TYPE "K" TRENCH REPAIR
(TRENCH NOT UNDER CONCRETE OR ASPHALT PAVEMENT)

TYPE "L" TRENCH REPAIR
(TRENCH NOT UNDER CONCRETE OR ASPHALT PAVEMENT)

TYPE "M" TRENCH REPAIR
(TRENCH NOT UNDER CONCRETE OR ASPHALT PAVEMENT)

TYPE "N" TRENCH REPAIR
(TRENCH NOT UNDER CONCRETE OR ASPHALT PAVEMENT)

TYPE "O" TRENCH REPAIR
(TRENCH NOT UNDER CONCRETE OR ASPHALT PAVEMENT)

TYPE "P" TRENCH REPAIR
(TRENCH NOT UNDER CONCRETE OR ASPHALT PAVEMENT)

TYPE "Q" TRENCH REPAIR
(TRENCH NOT UNDER CONCRETE OR ASPHALT PAVEMENT)

TYPE "R" TRENCH REPAIR
(TRENCH NOT UNDER CONCRETE OR ASPHALT PAVEMENT)

TYPE "S" TRENCH REPAIR
(TRENCH NOT UNDER CONCRETE OR ASPHALT PAVEMENT)

TYPE "T" TRENCH REPAIR
(TRENCH NOT UNDER CONCRETE OR ASPHALT PAVEMENT)

TYPE "U" TRENCH REPAIR
(TRENCH NOT UNDER CONCRETE OR ASPHALT PAVEMENT)

TYPE "V" TRENCH REPAIR
(TRENCH NOT UNDER CONCRETE OR ASPHALT PAVEMENT)

TYPE "W" TRENCH REPAIR
(TRENCH NOT UNDER CONCRETE OR ASPHALT PAVEMENT)

TYPE "X" TRENCH REPAIR
(TRENCH NOT UNDER CONCRETE OR ASPHALT PAVEMENT)

TYPE "Y" TRENCH REPAIR
(TRENCH NOT UNDER CONCRETE OR ASPHALT PAVEMENT)

TYPE "Z" TRENCH REPAIR
(TRENCH NOT UNDER CONCRETE OR ASPHALT PAVEMENT)

TYPE "AA" TRENCH REPAIR
(TRENCH NOT UNDER CONCRETE OR ASPHALT PAVEMENT)

TYPE "BB" TRENCH REPAIR
(TRENCH NOT UNDER CONCRETE OR ASPHALT PAVEMENT)

TYPE "CC" TRENCH REPAIR
(TRENCH NOT UNDER CONCRETE OR ASPHALT PAVEMENT)

TYPE "DD" TRENCH REPAIR
(TRENCH NOT UNDER CONCRETE OR ASPHALT PAVEMENT)

TYPE "EE" TRENCH REPAIR
(TRENCH NOT UNDER CONCRETE OR ASPHALT PAVEMENT)

TYPE "FF" TRENCH REPAIR
(TRENCH NOT UNDER CONCRETE OR ASPHALT PAVEMENT)

TYPE "GG" TRENCH REPAIR
(TRENCH NOT UNDER CONCRETE OR ASPHALT PAVEMENT)

TYPE "HH" TRENCH REPAIR
(TRENCH NOT UNDER CONCRETE OR ASPHALT PAVEMENT)

TYPE "II" TRENCH REPAIR
(TRENCH NOT UNDER CONCRETE OR ASPHALT PAVEMENT)

TYPE "JJ" TRENCH REPAIR
(TRENCH NOT UNDER CONCRETE OR ASPHALT PAVEMENT)

TYPE "KK" TRENCH REPAIR
(TRENCH NOT UNDER CONCRETE OR ASPHALT PAVEMENT)

TYPE "LL" TRENCH REPAIR
(TRENCH NOT UNDER CONCRETE OR ASPHALT PAVEMENT)

TYPE "MM" TRENCH REPAIR
(TRENCH NOT UNDER CONCRETE OR ASPHALT PAVEMENT)

TYPE "NN" TRENCH REPAIR
(TRENCH NOT UNDER CONCRETE OR ASPHALT PAVEMENT)

TYPE "OO" TRENCH REPAIR
(TRENCH NOT UNDER CONCRETE OR ASPHALT PAVEMENT)

TYPE "PP" TRENCH REPAIR
(TRENCH NOT UNDER CONCRETE OR ASPHALT PAVEMENT)

TYPE "QQ" TRENCH REPAIR
(TRENCH NOT UNDER CONCRETE OR ASPHALT PAVEMENT)

TYPE "RR" TRENCH REPAIR
(TRENCH NOT UNDER CONCRETE OR ASPHALT PAVEMENT)

TYPE "SS" TRENCH REPAIR
(TRENCH NOT UNDER CONCRETE OR ASPHALT PAVEMENT)

TYPE "TT" TRENCH REPAIR
(TRENCH NOT UNDER CONCRETE OR ASPHALT PAVEMENT)

TYPE "UU" TRENCH REPAIR
(TRENCH NOT UNDER CONCRETE OR ASPHALT PAVEMENT)

TYPE "VV" TRENCH REPAIR
(TRENCH NOT UNDER CONCRETE OR ASPHALT PAVEMENT)

TYPE "WW" TRENCH REPAIR
(TRENCH NOT UNDER CONCRETE OR ASPHALT PAVEMENT)

TYPE "XX" TRENCH REPAIR
(TRENCH NOT UNDER CONCRETE OR ASPHALT PAVEMENT)

TYPE "YY" TRENCH REPAIR
(TRENCH NOT UNDER CONCRETE OR ASPHALT PAVEMENT)

TYPE "ZZ" TRENCH REPAIR
(TRENCH NOT UNDER CONCRETE OR ASPHALT PAVEMENT)

TYPE "AA" TRENCH REPAIR
(TRENCH NOT UNDER CONCRETE OR ASPHALT PAVEMENT)

TYPE "BB" TRENCH REPAIR
(TRENCH NOT UNDER CONCRETE OR ASPHALT PAVEMENT)

TYPE "CC" TRENCH REPAIR
(TRENCH NOT UNDER CONCRETE OR ASPHALT PAVEMENT)

TYPE "DD" TRENCH REPAIR
(TRENCH NOT UNDER CONCRETE OR ASPHALT PAVEMENT)

TYPE "EE" TRENCH REPAIR
(TRENCH NOT UNDER CONCRETE OR ASPHALT PAVEMENT)

TYPE "FF" TRENCH REPAIR
(TRENCH NOT UNDER CONCRETE OR ASPHALT PAVEMENT)

TYPE "GG" TRENCH REPAIR
(TRENCH NOT UNDER CONCRETE OR ASPHALT PAVEMENT)

TYPE "HH" TRENCH REPAIR
(TRENCH NOT UNDER CONCRETE OR ASPHALT PAVEMENT)

TYPE "II" TRENCH REPAIR
(TRENCH NOT UNDER CONCRETE OR ASPHALT PAVEMENT)

TYPE "JJ" TRENCH REPAIR
(TRENCH NOT UNDER CONCRETE OR ASPHALT PAVEMENT)

TYPE "KK" TRENCH REPAIR
(TRENCH NOT UNDER CONCRETE OR ASPHALT PAVEMENT)

TYPE "LL" TRENCH REPAIR
(TRENCH NOT UNDER CONCRETE OR ASPHALT PAVEMENT)

TYPE "MM" TRENCH REPAIR
(TRENCH NOT UNDER CONCRETE OR ASPHALT PAVEMENT)

TYPE "NN" TRENCH REPAIR
(TRENCH NOT UNDER CONCRETE OR ASPHALT PAVEMENT)

TYPE "OO" TRENCH REPAIR
(TRENCH NOT UNDER CONCRETE OR ASPHALT PAVEMENT)

TYPE "PP" TRENCH REPAIR
(TRENCH NOT UNDER CONCRETE OR ASPHALT PAVEMENT)

TYPE "QQ" TRENCH REPAIR
(TRENCH NOT UNDER CONCRETE OR ASPHALT PAVEMENT)

TYPE "RR" TRENCH REPAIR
(TRENCH NOT UNDER CONCRETE OR ASPHALT PAVEMENT)

TYPE "SS" TRENCH REPAIR
(TRENCH NOT UNDER CONCRETE OR ASPHALT PAVEMENT)

TYPE "TT" TRENCH REPAIR
(TRENCH NOT UNDER CONCRETE OR ASPHALT PAVEMENT)

TYPE "UU" TRENCH REPAIR
(TRENCH NOT UNDER CONCRETE OR ASPHALT PAVEMENT)

TYPE "VV" TRENCH REPAIR
(TRENCH NOT UNDER CONCRETE OR ASPHALT PAVEMENT)

TYPE "WW" TRENCH REPAIR
(TRENCH NOT UNDER CONCRETE OR ASPHALT PAVEMENT)

TYPE "XX" TRENCH REPAIR
(TRENCH NOT UNDER CONCRETE OR ASPHALT PAVEMENT)

TYPE "YY" TRENCH REPAIR
(TRENCH NOT UNDER CONCRETE OR ASPHALT PAVEMENT)

TYPE "ZZ" TRENCH REPAIR
(TRENCH NOT UNDER CONCRETE OR ASPHALT PAVEMENT)

TYPE "AA" TRENCH REPAIR
(TRENCH NOT UNDER CONCRETE OR ASPHALT PAVEMENT)

TYPE "BB" TRENCH REPAIR
(TRENCH NOT UNDER CONCRETE OR ASPHALT PAVEMENT)

TYPE "CC" TRENCH REPAIR
(TRENCH NOT UNDER CONCRETE OR ASPHALT PAVEMENT)

TYPE "DD" TRENCH REPAIR
(TRENCH NOT UNDER CONCRETE OR ASPHALT PAVEMENT)

TYPE "EE" TRENCH REPAIR
(TRENCH NOT UNDER CONCRETE OR ASPHALT PAVEMENT)

TYPE "FF" TRENCH REPAIR
(TRENCH NOT UNDER CONCRETE OR ASPHALT PAVEMENT)

TYPE "GG" TRENCH REPAIR
(TRENCH NOT UNDER CONCRETE OR ASPHALT PAVEMENT)

TYPE "HH" TRENCH REPAIR
(TRENCH NOT UNDER CONCRETE OR ASPHALT PAVEMENT)

TYPE "II" TRENCH REPAIR
(TRENCH NOT UNDER CONCRETE OR ASPHALT PAVEMENT)

TYPE "JJ" TRENCH REPAIR
(TRENCH NOT UNDER CONCRETE OR ASPHALT PAVEMENT)

TYPE "KK" TRENCH REPAIR
(TRENCH NOT UNDER CONCRETE OR ASPHALT PAVEMENT)

TYPE "LL" TRENCH REPAIR
(TRENCH NOT UNDER CONCRETE OR ASPHALT PAVEMENT)

TYPE "MM" TRENCH REPAIR
(TRENCH NOT UNDER CONCRETE OR ASPHALT PAVEMENT)

TYPE "NN" TRENCH REPAIR
(TRENCH NOT UNDER CONCRETE OR ASPHALT PAVEMENT)

